

INDUSTRIAL COMPONENT DATA

DFK-PCV 5/ 7-GF-7,62 1716441 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-PCV 5/ 7-GF-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-PCV 5/ 7-GF-7,62
Catalog number	1716441
Category	Printed circuit board connector
Minimum order	10 Pcs
Document ID	EO-1A73CC1220
Generated	2026-08-01

Product Overview

Printed-circuit board connector

Wall pass-through housing, nominal section: 6 mm², color: green, nominal current: 41 A, dimensioning voltage (III/2): 630 V, contact surface: Tin, contact type: Male, Number of potentials: 7, Number of rows: 1, Number of poles per row: 7, number of connections: 7, family of articles: DFK-PCV 5/.. -GF, pitch: 7.62 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 5 mm, Stecksystem: POWER COMBICON 5, Locking: Screw locking, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1716441

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 547 (C-1-2013)

GTIN 4046356137065

Weight per Piece (excluding packing) 24.920 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [l] 19.54 mm

Width 87.96 mm

Pitch 7.62 mm

Dimension a 45.72 mm

Width [w] 87.96 mm

Height [h] 21.1 mm

Height 29.25 mm

Length of the solder pin 5 mm

Pin dimensions 0.8 x 1 mm

Pin spacing 7.62 mm

Length 19.54 mm

General

Range of articles DFK-PCV 5/...-GF

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 500 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 800 V

Connection in acc. with standard EN-VDE

Nominal current I_N 41 A

Maximum load current 41 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 7

Standards and Regulations

Connection in acc. with standard EN-VDE

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-PCV 5/ 7-GF-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.