

INDUSTRIAL COMPONENT DATA

GICV 2,5/ 8-GF-7,62 1859153 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: GICV 2,5/ 8-GF-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	GICV 2,5/ 8-GF-7,62
Catalog number	1859153
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-51FE1C62CF
Generated	2026-08-03

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: GICV 2.5/.. -GF, pitch: 7.62 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.6 mm, number of solder pins per potential: 2, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

PCB base strip, nominal cross-section: 2.5 mm², colour: green, rated current: 12 A, rated voltage (III/2): 630 V, contact surface: Sn, contact type: socket, number of potentials: 8, number of rows: 1, number of poles: 8, number of terminals: 8, article family: GICV 2.5/.. -GF, Pitch: 7.62 mm, Mounting: Wave Soldering, Pin Layout: Linear Pinning, Pin Length [P]: 3.6 mm, Number of Solder Pins per Potential: 2, Mating System: COMBICON MSTB 2.5, Mating Face Alignment: Standard, Latching: Screw Latch, Mounting Type: Threaded Flange, Packaging Type: Packed in a Box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1859153

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 347 (C-1-2013)

GTIN 4017918106218

Weight per Piece (excluding packing) 8.270 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 10.2 mm

Width 71.34 mm

Pitch 7.62 mm

Dimension a 53.34 mm

Width [w] 71.34 mm

Height [h] 22.6 mm

Height 19 mm

Length of the solder pin 3.6 mm

Pin dimensions 1.2 x 0.5 mm

Length 10.2 mm

General

Range of articles GICV 2,5/..-GF

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 500 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 8

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSP...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GICV 2,5/ 8-GF-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.