

## INDUSTRIAL COMPONENT DATA

# GMSTB 2,5/10-GF-7,62 1806300 PHOENIX CONTACT

## Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMSTB 2,5/10-GF-7,62



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | GMSTB 2,5/10-GF-7,62            |
| Catalog number  | 1806300                         |
| Category        | Printed circuit board connector |
| Minimum order   | 50 Pcs                          |
| Document ID     | EO-AA9E301689                   |
| Generated       | 2026-08-02                      |

### Product Overview

Feed-through header

Printed circuit board base case, nominal section: 2.5 mm<sup>2</sup>, color: green, nominal current: 12 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of potentials: 10, number of rows: 1, number of poles: 10, number of connections: 10, family of articles: GMSTB 2.5/.. -GF, pitch: 7.62 mm, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, pin arrangement: Linear pin arrangement, pin length [P]: 3.2 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

### Additional Product Information

Key Commercial Data

Orderkey 1806300

Packing unit 50 pc

Catalog page Page 343 (C-1-2013)

GTIN 4017918046972

Weight per Piece (excluding packing) 6.330 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [ l ] 12 mm

Width 86.78 mm

Pitch 7.62 mm

Dimension a 68.58 mm

Width [ w ] 86.78 mm

Height [ h ] 11.8 mm

Height 8.6 mm

Length of the solder pin 3.2 mm

Pin dimensions 1 x 1 mm

Length 12 mm

General

Range of articles GMSTB 2,5/...-GF

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 400 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 12 A

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 10

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss  
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC  
13.239121409

ETIM for 1806300 Co...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMSTB 2,5/10-GF-7,62 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.