


INDUSTRIAL COMPONENT DATA

GMSTB 2,5/ 8-G-7,62 1766181 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMSTB 2,5/ 8-G-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	GMSTB 2,5/ 8-G-7,62
Catalog number	1766181
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-7E2F8644CD
Generated	2026-08-02

Product Overview

Feed-through header

Printed circuit board base case, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: GMSTB 2.5/.. -G, pitch: 7.62 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.2 mm, number of soldering pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

PCB base strip, nominal cross-section: 2.5 mm², color: green, rated current: 12 A, rated voltage (III/2): 630 V, contact surface: Sn, contact type: pin, number of potentials: 8, number of rows: 1, number of poles: 8, number of terminals: 8, article family: GMSTB 2,5/.. -G, Pitch: 7.62 mm, Mounting: Wave Soldering, Pin Layout: Linear Pinning, Pin Length [P]: 3.23 mm, Number of Solder Pins Per Potential: 1, Plug-in System: COMBICON MSTB 2.5, Mating Face Orientation: Standard, Locking: None, Mounting Type: None, Packaging Type: Packed in a Box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1766181

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 342 (C-1-2013)

GTIN 4017918032203

Weight per Piece (excluding packing) 3.380 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 12 mm

Width 59.16 mm

Pitch 7.62 mm

Dimension a 53.34 mm

Width [w] 59.16 mm

Height [h] 11.8 mm

Height 8.6 mm

Length of the solder pin 3.2 mm

Pin dimensions 1 x 1 mm

Length 12 mm

General

Range of articles GMSTB 2,5/..-G

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 400 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 8

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1766181 Connectors (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMSTB 2,5/ 8-G-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.