


INDUSTRIAL COMPONENT DATA

IMCV 1,5/ 7-G-3,81 1875470 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: IMCV 1,5/ 7-G-3,81



Manufacturer	PHOENIX CONTACT
MPN / Reference	IMCV 1,5/ 7-G-3,81
Catalog number	1875470
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-398CD6DF8B
Generated	2026-08-02

Product Overview

Feed-through header

Base housing printed circuit board, nominal section: 1.5 mm², colour: green, rated current: 8 A, sizing voltage (III/2): 160 V, surface contacts: Tin, contact type: Connecting female, Number of potentials: 7, Number of rows: 1, Number of poles per row: 7, number of connections: 7, article family: IMCV 1.5/.. -G, pitch: 3.81 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, Stecksystem: MINI COMBICON, Locking: sin, packing type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1875470

Packing unit 50 pc

Catalog page Page 239 (C-1-2013)

GTIN 4017918133979

Weight per Piece (excluding packing) 2.460 g

Custom tariff number 85366930

Country of origin PL (Poland)

Dimensions

Length [L] 6.85 mm

Width 27.46 mm

Pitch 3.81 mm

Dimension a 22.86 mm

Width [w] 27.46 mm

Height [h] 18 mm

Height 14.5 mm

Length of the solder pin 3.5 mm

Pin dimensions 0.62 x 1.12 mm

Pin spacing 3.81 mm

Length 6.85 mm

General

Range of articles IMCV 1,5/..-G

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Maximum load current 8 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 7

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC

13.239121409

ETIM for 1875470 Connectors....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IMCV 1,5/ 7-G-3,81 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.