

INDUSTRIAL COMPONENT DATA

IPC 16/ 5-GU-10,16 1969881 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: IPC 16/ 5-GU-10,16



Manufacturer	PHOENIX CONTACT
MPN / Reference	IPC 16/ 5-GU-10,16
Catalog number	1969881
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-AF6081369E
Generated	2026-07-31

Product Overview

Feed-through header

Printed circuit board base case, nominal section: 16 mm², color: green, nominal current: 76 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Female, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: IPC 16/.. -GU, pitch: 10.16 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4 mm, number of soldering pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: inverted, locking: without, fixing type: without, packaging type: box-packed, connection direction parallel to printed circuit board; Plug-in part rotated 180° with respect to the socket shaft.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1969881

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 571 (C-1-2013)

GTIN 4017918948634

Weight per Piece (excluding packing) 19.340 g

Custom tariff number 85366930

Country of origin PL (Poland)

Dimensions

Length [l] 32.1 mm

Width 51.6 mm

Pitch 10.16 mm

Dimension a 40.64 mm

Width [w] 51.6 mm

Height [h] 17.4 mm

Height 13.6 mm

Length of the solder pin 4 mm

Pin dimensions 0.8 x 1.2 mm

Pin spacing 10.16 mm

Length 32.1 mm

General

Range of articles IPC 16/..-GU

Insulating material group I

Rated surge voltage (III/3) 8 kV

Rated surge voltage (III/2) 8 kV

Rated surge voltage (II/2) 8 kV

Rated voltage (III/3) 1000 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Nominal current I_N 76 A

Maximum load current 76 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 5

Standards and Regulations

Connection in acc. with standard CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1969...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IPC 16/ 5-GU-10,16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.