

INDUSTRIAL COMPONENT DATA

MC 1,5/ 9-G-3,5-RN 1731743 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 9-G-3,5-RN



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 9-G-3,5-RN
Catalog number	1731743
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-7C9EC9B14F
Generated	2026-07-31

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 9, number of rows: 1, number of poles: 9, number of connections: 9, family of articles: MC 1.5/.. -G-RN, pitch: 3.5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Snap-in lock, fixing type: Socket protrusion, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1731743

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 225 (C-1-2013)

GTIN 4046356159357

Weight per Piece (excluding packing) 2.080 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 9.2 mm

Width 35.1 mm

Pitch 3.5 mm

Dimension a 28 mm

Width [w] 35.1 mm

Height [h] 10.65 mm

Height 7.25 mm

Length of the solder pin 3.4 mm

Pin dimensions 0.8 x 0.8 mm

Length 9.2 mm

General

Range of articles MC 1,5/..-G-RN

Insulating material group IIIa

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 250 V

Connection in acc. with standard EN-VDE

Nominal current I_N 8 A

Maximum load current 8 A

Insulating material PBT

Flammability rating according to UL 94 V0

Color green

Number of positions 9

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSP...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 9-G-3,5-RN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.