

INDUSTRIAL COMPONENT DATA

MCD 0,5/ 6-G1-2,5 1894846 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCD 0,5/ 6-G1-2,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCD 0,5/ 6-G1-2,5
Catalog number	1894846
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-86A2E8A72F
Generated	2026-07-31

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 0.5 mm², color: green, nominal current: 4 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 12, number of rows: 2, number of poles: 6, number of connections: 12, family of articles: MCD 0.5/.. -G1, pitch: 2.5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.8 mm, number of soldering pins per potential: 1, plug-in system: COMBICON FK-MC 0.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1894846

Packing unit 50 pc

Catalog page Page 173 (C-1-2013)

GTIN 4017918162115

Weight per Piece (excluding packing) 5.450 g

Custom tariff number 85366930

Country of origin PL (Poland)

Dimensions

Length [L] 17.5 mm

Width 16.9 mm

Pitch 2.5 mm

Dimension a 12.5 mm

Width [w] 16.9 mm

Height [h] 25.7 mm

Height 21.9 mm

Length of the solder pin 3.8 mm

Pin dimensions 0.8 x 0.8 mm

Length 17.5 mm

General

Range of articles MCD 0,5/-G1

Insulating material group I

Rated surge voltage (III/3) 1.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 80 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 4 A

Maximum load current 4 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 6

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1894846 Connectors (EC002637)

Feature Name

F...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCD 0,5/ 6-G1-2,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.