


INDUSTRIAL COMPONENT DATA

MCDN 1,5/ 3-G1-3,5 RNP26THR 1953415 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCDN 1,5/ 3-G1-3,5 RNP26THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCDN 1,5/ 3-G1-3,5 RNP26THR
Catalog number	1953415
Category	Printed circuit board connector
Minimum order	80 Pcs
Document ID	EO-1CF2C7C202
Generated	2026-08-03

Product Overview

Feed-through header

Base housing printed circuit board, nominal section: 1.5 mm², color: black, rated current: 8 A, sizing voltage (III/2): 160 V, surface contacts: Tin, contact type: Male, Number of potentials: 6, Number of rows: 2, Number of poles per row: 3, number of connections: 6, article family: MCDN 1.5/.. -G1-RN-THR, pitch: 3.5 mm, mounting: Welding THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, Stecksystem: MINI COMBICON, Locking: Locking by lace, type of packaging: boxed packaging, Article with lace protrusion. The pin length is 2.6 mm. For user information and design recommendations on Through Hole Reflow technology, see under:"Downloads"

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1953415

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 219 (C-1-2013)

GTIN 4017918919443

Weight per Piece (excluding packing) 2.420 g

Custom tariff number 85366930

Country of origin BG (Bulgaria)

Dimensions

Length [l] 13.3 mm

Width 14.2 mm

Pitch 3.5 mm

Dimension a 7 mm

Width [w] 14.2 mm

Height [h] 15.2 mm

Height 16 mm

Length of the solder pin 2.6 mm

Pin dimensions 0.8 x 0.8 mm

Pin spacing 3.50 mm

Length 13.3 mm

General

Range of articles MCDN 1,5/-G1-RN-THR

Insulating material group IIIa

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 250 V

Connection in acc. with standard EN-VDE

Nominal current I_N 8 A

Maximum load current 8 A (per position)

Insulating material LCP

Flammability rating according to UL 94 V0

Color black

Number of positions 3

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

ClassificationseCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.013912140...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCDN 1,5/ 3-G1-3,5 RNP26THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.