


INDUSTRIAL COMPONENT DATA

MCDNV 1,5/15-G1-3,81 P14THR 1750232 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCDNV 1,5/15-G1-3,81 P14THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCDNV 1,5/15-G1-3,81 P14THR
Catalog number	1750232
Category	Printed circuit board connector
Minimum order	40 Pcs
Document ID	EO-EE7402BA65
Generated	2026-07-29

Product Overview

Feed-through header

Printed circuit board base case, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 30, number of rows: 2, number of poles: 15, number of connections: 30, family of articles: MCDNV 1.5/.. -G1-THR, pitch: 3.81 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 1.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: box-packed, Pin length is 1.4 mm. For user information and design recommendations on Through Hole Reflow technology, please refer to: "Downloads".

PCB base strip, nominal cross-section: 1.5 mm², colour: black, rated current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact type: pin, number of potentials: 30, number of rows: 2, number of poles: 15, number of terminals: 30, article family: MCDNV 1.5/.. -G1-THR, Pitch: 3.81 mm, Mounting: THR Soldering / Wave Soldering, Pin Layout: Linear Pinning, Pin Length [P]: 1.4 mm, Number of Solder Pins per Potential: 1, Mating System: COMBICON FMC 1.5 - MCDN 1.5, Mating Face Alignment: Standard, Latching: None, Mounting Type: None, Packaging Type: Packed in a Box, Pin Length is 1.4 mm. User information and design recommendations for Through Hole R...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1750232

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 220 (C-1-2013)

GTIN 4046356314664

Weight per Piece (excluding packing) 9.000 g

Custom tariff number 85366930

Country of origin BG (Bulgaria)

Dimensions

Length [l] 15.2 mm

Width 58.24 mm

Pitch 3.81 mm

Dimension a 53.34 mm

Width [w] 58.24 mm

Height [h] 14.7 mm

Height 13.3 mm

Length of the solder pin 1.4 mm

Pin dimensions 0.8 x 0.8 mm

Pin spacing 8.30 mm

Length 15.2 mm

General

Range of articles MCDNV 1,5/-G1-THR

Insulating material group IIIa

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 200 V

Rated voltage (II/2) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Maximum load current 8 A (per position)

Insulating material LCP

Flammability rating according to UL 94 V0

Color black

Number of positions 15

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.0901...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCDNV 1,5/15-G1-3,81 P14THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.