


INDUSTRIAL COMPONENT DATA

MCDV 1,5/ 2-G1F-3,81 1842762 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCDV 1,5/ 2-G1F-3,81



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCDV 1,5/ 2-G1F-3,81
Catalog number	1842762
Category	Printed circuit board connector
Minimum order	80 Pcs
Document ID	EO-4D804362C6
Generated	2026-08-02

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 2, number of poles: 2, number of connections: 4, family of articles: MCDV 1.5/.. -G1F, pitch: 3.81 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed packaging, In the case of a combination with MCV plug-in parts, an MCVW connector and an MCVR connector must be used, respectively.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1842762

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 237 (C-1-2013)

GTIN 4017918111977

Weight per Piece (excluding packing) 5.550 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 22.7 mm

Width 18.01 mm

Pitch 3.81 mm

Dimension a 3.81 mm

Width [w] 18.01 mm

Height [h] 25.3 mm

Height 21.9 mm

Length of the solder pin 3.4 mm

Pin dimensions 0.8 x 0.8 mm

Pin spacing 15.24 mm

Length 22.7 mm

General

Range of articles MCDV 1,5/..-G1F

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Maximum load current 8 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 2

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

ClassificationseCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCDV 1,5/ 2-G1F-3,81 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.