

INDUSTRIAL COMPONENT DATA

MCO 1,5/ 4-GL-3,81 1861743 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCO 1,5/ 4-GL-3,81



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCO 1,5/ 4-GL-3,81
Catalog number	1861743
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-54207B0257
Generated	2026-07-31

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: MCO 1.5/.. -GL, pitch: 3.81 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1861743

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 230 (C-1-2013)

GTIN 4017918133511

Weight per Piece (excluding packing) 2.040 g

Custom tariff number 85366930

Country of origin PL (Poland)

Dimensions

Length [l] 29.43 mm

Width 7.25 mm

Pitch 3.81 mm

Dimension a 11.43 mm

Width [w] 7.25 mm

Height [h] 20.44 mm

Length of the solder pin 3 mm

Pin dimensions 0.9 x 0.32 mm

Length 29.43 mm

General

Range of articles MCO 1,5/-GL

Insulating material group IIIa

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 125 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 200 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Insulating material PA (PBT)

Flammability rating according to UL 94 V0

Color green

Number of positions 4

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1861743 Connectors (EC002637)

Feat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCO 1,5/ 4-GL-3,81 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.