


## INDUSTRIAL COMPONENT DATA

# MCV 0,5/ 2-G-2,5 THT 1963531 PHOENIX CONTACT

## Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 0,5/ 2-G-2,5 THT



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | MCV 0,5/ 2-G-2,5 THT            |
| Catalog number  | 1963531                         |
| Category        | Printed circuit board connector |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-9F4A359851                   |
| Generated       | 2026-07-31                      |

### Product Overview

MCV 0,5/ 2-G-2,5 THT 1963531 PHOENIX CONTACT Feed-through header

## STRUCTURED PRODUCT DATA

### Technical Specifications

| TECHNICAL ATTRIBUTE                       | VALUE           |
|-------------------------------------------|-----------------|
| Connector model (EF007495)                | Fixed connector |
| Contact type (EF001587)                   | Pin             |
| Number of poles (EF001391)                | 2               |
| Number of plug-in contact rows (EF006935) | 1               |
| Modular spacing contacts (EF007326)       | 2.5 mm          |
| Modular spacing connections (EF006827)    | 2.5 mm          |
| Rated current I <sub>n</sub> (EF008250)   | 4 A             |
| Rated voltage (EF000228)                  | 160 V           |
| Rated surge voltage (EF002993)            | 2.5 kV          |
| Over voltage category (EF006785)          | III             |
| Pollution degree (EF006786)               | 2               |
| Material of contact surface (EF004020)    | Tin             |
| Type of electric connection (EF003961)    | Other           |
| Diameter connection pin (EF006823)        | 1.4 mm          |
| Length pin (EF006825)                     | 3.5 mm          |

**CONTINUED****Technical Specifications**

| TECHNICAL ATTRIBUTE                                                      | VALUE            |
|--------------------------------------------------------------------------|------------------|
| Material insulation body (EF007543)                                      | Other            |
| Housing colour (EF000136)                                                | Black            |
| Inflammability class of insulation material according to UL94 (EF002521) | V0               |
| Operating temperature (EF002393)                                         | -40 °C           |
| Type of fastening (EF002442)                                             | Other            |
| Type of banding (EF007011)                                               | Carton (for SMD) |

**Classification & Catalog Path**

|              |                                        |
|--------------|----------------------------------------|
| eCl@ss 7.1   | 21043711                               |
| eCl@ss 8.0   | 21043711                               |
| eCl@ss 9.0   | 21043711                               |
| ETIM 5.0     | EC002246                               |
| ETIM 6.0     | EC002246                               |
| ETIM 7.0     | EC002246                               |
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

**Additional Product Information****Feed-through header**

Printed circuit board base housing, nominal section: 0.5 mm<sup>2</sup>, color: black, nominal current: 4 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: MCV 0.5/.. -G-THT, pitch: 2.5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON FK-MC 0.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed, More user information and design recommendations on Through Hole Reflow technology can be found at: Downloads

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / MCV 0,5/ 2-G-2,5 THT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.