

INDUSTRIAL COMPONENT DATA

MCV 1,5/11-GF-3,81 P14 THR 1707308 PHOENIX CONTACT Header, Nominal current: 8 A, Rated voltage (III/2): 160 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/11-GF-3,81 P14 THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/11-GF-3,81 P14 THR
Catalog number	1707308
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-9CD323949E
Generated	2026-08-02

Product Overview

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 11, Pitch: 3.81 mm, Color: black, Contact surface: Tin, Mounting: SMD/THT/THR, User information and design recommendations for through hole reflow technology can be found under "Downloads"

Printed circuit board base case, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 11, number of rows: 1, number of poles: 11, number of connections: 11, family of articles: MCV 1.5/.. -GF-THR, pitch: 3.81 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 1.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Screw lock, fastening type: Overhead fastening (thread), packaging type: boxed, Further user information and design recommendations on Through Hole Reflow technology can be found at: Downloads

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Dimensions

Length 7.25 mm

Pitch 3.81 mm

Dimension a 38.1 mm

Width 51.9 mm

Constructional height 9.2 mm

Height 10.6 mm

Length of the solder pin 1.4 mm

Pin dimensions 0,8 x 0,8 mm

Hole diameter 1.4 mm

General

Range of articles MCV 1,5/...-GF-THR

Insulating material group IIIa

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 250 V

Connection in acc. with standard EN-VDE

Nominal current I_N 8 A

Maximum load current 8 A

Insulating material LCP

Flammability rating according to UL 94 V0

Color black

Number of positions 11

ETIM for 1707308 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

11

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

3.81 mm

Modular spacing connections (EF006827)

3.81 mm

Rated current I_n (EF008250)

8 A

Rated voltage (EF000228)

160 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Tin

Type of electric connection (EF003961)

Other

Diameter connection pin (EF006823)

1.4 mm

Length pin (EF006825)

1.4 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Black

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of fastening (EF002442)

O...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/11-GF-3,81 P14 THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.