

INDUSTRIAL COMPONENT DATA

MCV 1,5/ 8-GF-5,08 1847673 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 8-GF-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 8-GF-5,08
Catalog number	1847673
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-1E30B94F8F
Generated	2026-08-02

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: MCV 1.5/.. -GF, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1847673

Packing unit 50 pc

Catalog page Page 249 (C-1-2013)

GTIN 4017918113803

Weight per Piece (excluding packing) 3.470 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [L] 7.25 mm

Width 49.76 mm

Pitch 5.08 mm

Dimension a 35.56 mm

Width [w] 49.76 mm

Height [h] 12.6 mm

Height 9.2 mm

Length of the solder pin 3.4 mm

Pin dimensions 0.8 x 0.8 mm

Length 7.25 mm

General

Range of articles MCV 1,5/..-GF

Insulating material group IIIa

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Maximum load current 8 A

Insulating material PBT

Flammability rating according to UL 94 V0

Color green

Number of positions 8

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 184...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 8-GF-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.