

**INDUSTRIAL COMPONENT DATA**

# MDSTB 2,5/10-G1-5,08 1762457 PHOENIX CONTACT

## Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MDSTB 2,5/10-G1-5,08



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | MDSTB 2,5/10-G1-5,08            |
| Catalog number  | 1762457                         |
| Category        | Printed circuit board connector |
| Minimum order   | 50 Pcs                          |
| Document ID     | EO-88B5B8E0E6                   |
| Generated       | 2026-08-02                      |

### Product Overview

Feed-through header

Printed circuit board base case, nominal section: 2.5 mm<sup>2</sup>, color: green, nominal current: 10 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 20, number of rows: 2, number of poles: 10, number of connections: 20, article family: MDSTB 2.5/.. -G1, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: box-packed, In the case of a combination with MVSTB or FKCV plug-in parts, an MVSTBW (or FKCVW) connector and an MVSTBR (or FKCVR) connector must be used, respectively. A combination with TMSTBP plug-in parts is not possible!

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; PCB Connectors (PCC)

### Additional Product Information

Key Commercial Data

Orderkey 1762457

Packing unit 50 pc

Catalog page Page 329 (C-1-2013)

GTIN 4017918031053

Weight per Piece (excluding packing) 15.920 g

Custom tariff number 85366930

Country of origin GR (Greece)

**Dimensions**

Length [ l ] 22 mm

Width 52.36 mm

Pitch 5.08 mm

Dimension a 45.72 mm

Width [ w ] 52.36 mm

Height [ h ] 32 mm

Height 28.5 mm

Length of the solder pin 3.5 mm

Pin dimensions 1 x 1 mm

Length 22 mm

**General**

Range of articles MDSTB 2,5/..-G1

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 10 A

Maximum load current 10 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 10

**Standards and Regulations**

Connection in acc. with standard EN-VDE

**CSA**

Flammability rating according to UL 94 V0

**Environmental Product Compliance**

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

**Classifications**eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss  
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC  
13.239121409

ETIM for 1762457 Connectors (EC002637)

**Feature Name**

Featur...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MDSTB 2,5/10-G1-5,08 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.