


## INDUSTRIAL COMPONENT DATA

# MDSTB 2,5/ 4-G1 1736690 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MDSTB 2,5/ 4-G1



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | MDSTB 2,5/ 4-G1                 |
| Catalog number  | 1736690                         |
| Category        | Printed circuit board connector |
| Minimum order   | 50 Pcs                          |
| Document ID     | EO-3A510712DD                   |
| Generated       | 2026-08-01                      |

## Product Overview

### Feed-through header

Printed circuit board base housing, nominal section: 2.5 mm<sup>2</sup>, color: green, nominal current: 10 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 8, number of rows: 2, number of poles: 4, number of connections: 8, family of articles: MDSTB 2.5/..-G1, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: box-packed, In the case of a combination with MVSTB or FKCV plug-in parts, an MVSTBW (or FKCVW) connector and an MVSTBR (or FKCVR) connector must be used, respectively. A combination with TMSTBP plug-in parts is not possible!

PCB headers, nominal cross section: 2.5 mm<sup>2</sup>, color: green, nominal current: 10 A, rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Pin, number of potentials: 8, number of rows: 2, number of positions: 4, number of connections: 8, product range: MDSTB 2,5/..-G1, pitch: 5 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.3 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2,5, Pin connector pattern alignment: Standard, locking: without, mounting: without, type of packaging: packed in cardboard, In com...

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; PCB Connectors (PCC)

## Additional Product Information

Technical dataProduct propertiesProduct type PCB headers

Product family MDSTB 2,5/..-G1

Product line COMBICON Connectors M

Type Standard  
Number of positions 4  
Pitch 5 mm  
Number of connections 8  
Number of rows 2  
Number of potentials 8  
Mounting flange without  
Pin layout Linear pinning  
Solder pins per potential 1  
Data management status  
Article revision 03  
Electrical propertiesNominal current IN 10 A  
Nominal voltage UN 320 V  
Contact resistance 2.2 m?  
Rated voltage (III/3) 250 V  
Rated surge voltage (III/3) 4 kV  
Rated voltage (III/2) 320 V  
Rated surge voltage (III/2) 4 kV  
Rated voltage (II/2) 630 V  
Rated surge voltage (II/2) 4 kV  
MountingMounting type Wave soldering  
Pin layout Linear pinning  
Material specificationsMaterial data - contact  
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201  
Contact material Cu alloy  
Surface characteristics Tin-plated  
Metal surface contact area (top layer) Tin (5 - 7 µm Sn)  
Metal surface contact area (middle layer) Nickel (2 - 3 µm Ni)  
Metal surface soldering area (top layer) Tin (5 - 7 µm Sn)  
Metal surface soldering area (middle layer) Nickel (2 - 3 µm Ni)  
Material data - housing  
Color (Housing) green (6021)  
Insulating material PA  
Insulating material group I  
CTI according to IEC 60112 600  
Flammability rating according to UL 94 V0  
Glow wire flammability index GWFI according to EN 60695-2-12 850  
Glow wire ignition temperature GWIT according to EN 60695-2-13 775  
Temperature for the ball pressure test according to EN 60...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MDSTB 2,5/ 4-G1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.