


INDUSTRIAL COMPONENT DATA

MSTB 2,5 HC/12-GF 1924075 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTB 2,5 HC/12-GF



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTB 2,5 HC/12-GF
Catalog number	1924075
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-663165DF5F
Generated	2026-08-02

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 2.5 mm², color: green, nominal current: 16 A (see derating curve), nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, family of articles: MSTB 2.5 HC/.. -GF, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5 HC, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1924075

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 497 (C-1-2013)

GTIN 4017918600266

Weight per Piece (excluding packing) 4.980 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 12 mm

Width 70 mm

Pitch 5 mm

Dimension a 55 mm

Width [w] 70 mm

Height [h] 12.1 mm

Height 8.6 mm

Length of the solder pin 3.5 mm

Pin dimensions 1 x 1 mm

Pin spacing 5.00 mm

Length 12 mm

General

Range of articles MSTB 2,5 HC/..-GF

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current I_N 16 A (see derating curve)

Maximum load current 16 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 12

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810U...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTB 2,5 HC/12-GF with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.