

**INDUSTRIAL COMPONENT DATA**

# MSTBO 2,5/ 2-G1L KMGY 2854788 PHOENIX CONTACT

## Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBO 2,5/ 2-G1L KMGY



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | MSTBO 2,5/ 2-G1L KMGY           |
| Catalog number  | 2854788                         |
| Category        | Printed circuit board connector |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-C2C4EAF3C9                   |
| Generated       | 2026-08-01                      |

### Product Overview

MSTBO 2,5/ 2-G1L KMGY 2854788 PHOENIX CONTACT Feed-through header

**STRUCTURED PRODUCT DATA**

### Technical Specifications

| TECHNICAL ATTRIBUTE          | VALUE            |
|------------------------------|------------------|
| Type of accessory/spare part | Charger          |
| Mains voltage                | 100 V - 240 V AC |
| Suitable for                 | CF-CRIMPHANDY    |
| Output voltage               | 12 V DC          |
| Charging current             | 2 A              |

### Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| eCl@ss 7.1   | 21043711                       |
| eCl@ss 8.0   | 21043711                       |
| eCl@ss 9.0   | 21043711                       |
| ETIM 5.0     | EC002246                       |
| ETIM 6.0     | EC002246                       |
| ETIM 7.0     | EC002246                       |
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Feed-through header

Printed circuit board base housing, nominal section: 2.5 mm<sup>2</sup>, color: luminous gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: MSTBO 2.5/.. -G1L, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, lock: without, packaging type: boxed packed, Item with side pin output on the left

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBO 2,5/ 2-G1L KMGY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.