

INDUSTRIAL COMPONENT DATA

MSTBVA 2,5/18-G-5,08-LR 1809429 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBVA 2,5/18-G-5,08-LR



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBVA 2,5/18-G-5,08-LR
Catalog number	1809429
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-9FACD83C5F
Generated	2026-07-31

Product Overview

Printed-circuit board connector

Printed circuit board base case, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 18, number of rows: 1, number of poles: 18, number of connections: 18, family of articles: MSTBVA 2.5/.. -G-LR, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of soldering pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: Snap lock, fixing type: Lock & Release, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1809429

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4046356703673

Weight per Piece (excluding packing) 8.500 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [L] 8.6 mm

Width 101.6 mm

Pitch 5.08 mm

Dimension a 86.36 mm

Width [w] 101.6 mm

Height [h] 15.9 mm

Height 12 mm

Length of the solder pin 3.9 mm

Pin dimensions 1 x 1 mm

Length 8.6 mm

General

Range of articles MSTBVA 2,5/..-G-LR

Insulating material group IIIa

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Maximum load current 12 A

Insulating material PBT

Flammability rating according to UL 94 V0

Color green

Number of positions 18

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1809429 Connectors (EC002637)

Feature...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBVA 2,5/18-G-5,08-LR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.