


INDUSTRIAL COMPONENT DATA

MSTBVA 2,5/ 9-G-5,08 1755804 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBVA 2,5/ 9-G-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBVA 2,5/ 9-G-5,08
Catalog number	1755804
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-DD0FA2645F
Generated	2026-07-29

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 9, number of rows: 1, number of poles: 9, number of connections: 9, family of articles: MSTBVA 2.5/.. -G, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 9, pitch: 5.08 mm, color: green, contact surface: Tin, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.9 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1755804

Packing unit 1 pc

Minimum order quantity 100 pc

Catalog page Page 315 (C-1-2013)

GTIN 4017918029388

Weight per Piece (excluding packing) 3.400 g

Custom tariff number 85366930
Country of origin DE (Germany)
Drawings
Electrical parameters
Material data - housing
Dimensions for PCB design
Ambient conditions
Mechanical tests (A)
Climatic tests (D)
Standards and Regulations
Classifications
Item properties
Material data - contact
Dimensions for the product
Packaging information
Air clearances and creepage distances
Durability tests (B)
Environmental and durability tests (E)
Environmental Product Compliance
Drawings
Drilling diagram
Diagram
Type: TFKC 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Diagram
Type: TVMSTB 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Back to topItem properties
Brief article description Feed-through header
Plug-in system CLASSIC COMBICON
Type of contact Male connector
Range of articles MSTBVA 2,5/...-G
Pitch 5.08 mm
Number of positions 9
Mounting type Wave soldering
Pin layout Linear pinning
Locking without
Number of levels 1
Number of connections 9
Number of potentials 9
Back to topElectrical parameters
Nominal current 12 A
Nom. voltage 320 V
Rated voltage 320 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 630 V
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV

[Back to top](#)Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC J...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBVA 2,5/ 9-G-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.