


INDUSTRIAL COMPONENT DATA

MSTBVA 2,5/ 9-G-5,08-RN 1936089 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBVA 2,5/ 9-G-5,08-RN



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBVA 2,5/ 9-G-5,08-RN
Catalog number	1936089
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-DC98284379
Generated	2026-08-02

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 9, number of rows: 1, number of poles: 9, number of connections: 9, family of articles: MSTBVA 2.5/.. -G-RN, pitch: 5.08 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: Snap-in lock, fixing type: Socket protrusion, packaging type: box-packed, Item with lace protrusion

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1936089

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 316 (C-1-2013)

GTIN 4017918822071

Weight per Piece (excluding packing) 3.650 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 8.6 mm

Width 51.54 mm

Pitch 5.08 mm

Dimension a 40.64 mm

Width [w] 51.54 mm

Height [h] 15.9 mm

Height 12 mm

Length of the solder pin 3.9 mm

Pin dimensions 1 x 1 mm

Length 8.6 mm

General

Range of articles MSTBVA 2,5/..-G-RN

Insulating material group IIIa

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Maximum load current 12 A

Insulating material PBT

Flammability rating according to UL 94 V0

Color green

Number of positions 9

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

ClassificationseCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1936089 Conn...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBVA 2,5/ 9-G-5,08-RN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.