


## INDUSTRIAL COMPONENT DATA

# PCV 4/ 9-G-7,62 1804755 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: PCV 4/ 9-G-7,62



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | PCV 4/ 9-G-7,62                 |
| Catalog number  | 1804755                         |
| Category        | Printed circuit board connector |
| Minimum order   | 50 Pcs                          |
| Document ID     | EO-A9042DA832                   |
| Generated       | 2026-08-08                      |

## Product Overview

Feed-through header

Printed circuit board base case, nominal section: 4 mm<sup>2</sup>, color: green, nominal current: 20 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of potentials: 9, number of rows: 1, number of poles: 9, number of connections: 9, family of articles: PCV 4/..-G, pitch: 7.62 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 5 mm, number of solder pins per potential: 2, plug-in system: COMBICON PC 4, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: box-packed, Clamping flange: Accessory, Code 1827570

PCB headers, nominal cross section: 4 mm<sup>2</sup>, color: green, nominal current: 20 A, rated voltage (III/2): 630 V, contact surface: Sn, contact connection type: Pin, number of potentials: 9, number of rows: 1, number of positions: 9, number of connections: 9, product range: PCV 4/..-G, pitch: 7.62 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 5 mm, number of solder pins per potential: 2, plug-in system: COMBICON PC 4, Pin connector pattern alignment: Standard, locking: without, mounting: without, type of packaging: packed in cardboard, Mounting flange: Accessory Item No. 1827570

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

## Additional Product Information

Technical dataProduct propertiesProduct type PCB headers

Product family PCV 4/..-G

Product line COMBICON Connectors L

Type Standard  
Number of positions 9  
Pitch 7.62 mm  
Number of connections 9  
Number of rows 1  
Number of potentials 9  
Mounting flange without  
Pin layout Linear pinning  
Solder pins per potential 2  
Data management status  
Article revision 04  
Electrical propertiesNominal current IN 20 A  
Nominal voltage UN 630 V  
Contact resistance 0.45 m?  
Rated voltage (III/3) 400 V  
Rated surge voltage (III/3) 6 kV  
Rated voltage (III/2) 630 V  
Rated surge voltage (III/2) 6 kV  
Rated voltage (II/2) 630 V  
Rated surge voltage (II/2) 6 kV  
MountingMounting type Wave soldering  
Pin layout Linear pinning  
Material specificationsMaterial data - contact  
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201  
Contact material Cu alloy  
Surface characteristics Tin-plated  
Metal surface contact area (top layer) Tin (5 - 10 µm Sn)  
Metal surface contact area (middle layer) Nickel (2 - 5 µm Ni)  
Metal surface soldering area (top layer) Tin (5 - 10 µm Sn)  
Metal surface soldering area (middle layer) Nickel (2 - 5 µm Ni)  
Material data - housing  
Color (Housing) green (6021)  
Insulating material PA  
Insulating material group I  
CTI according to IEC 60112 600  
Flammability rating according to UL 94 V0  
Glow wire flammability index GWFI according to EN 60695-2-12 850  
Glow wire ignition temperature GWIT according to EN 60695-2-13 775  
Temperature for the ball pressure test according to EN 6...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PCV 4/ 9-G-7,62 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.