


INDUSTRIAL COMPONENT DATA

SMSTB 2,5/ 5-G 1769269 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMSTB 2,5/ 5-G



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMSTB 2,5/ 5-G
Catalog number	1769269
Category	Printed circuit board connector
Minimum order	2000 Pcs
Document ID	EO-152EFEDEF7
Generated	2026-08-02

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: SMSTB 2.5/.. -G, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

PCB socket, nominal cross-section: 2.5 mm², colour: green, rated current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Sn, contact connection type: plug, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, product series: SMSTB 2.5/.. -G, pitch: 5 mm, mounting: Wave soldering, pin layout: Linear pinning, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug system: COMBICON MSTB 2.5, Insertion pin orientation: Standard, locking: none, fixing type: none, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1769269

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 318 (C-1-2013)

GTIN 4017918034580

Weight per Piece (excluding packing) 2.810 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 16.5 mm

Width 25 mm

Pitch 5 mm

Dimension a 20 mm

Width [w] 25 mm

Height [h] 18.3 mm

Height 14.8 mm

Length of the solder pin 3.5 mm

Pin dimensions 1 x 1 mm

Length 16.5 mm

General

Range of articles SMSTB 2,5/...-G

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 5

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMSTB 2,5/ 5-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.