

INDUSTRIAL COMPONENT DATA

HC-B 16-TMQ-H-O1STM32S 1460184 PHOENIX CONTACT HEAVYCON B16 sleeve housing, with double locking latch, heigh..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 16-TMQ-H-O1STM32S



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 16-TMQ-H-O1STM32S
Catalog number	1460184
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-09B47A9415
Generated	2026-08-05

Product Overview

HEAVYCON B16 sleeve housing, with double locking latch, height 72 mm, with thread 1 x M32, lateral cable outlet
HEAVYCON B16 aerial housing, with transverse lock, height 72 mm, with 1 M32 thread, side cable outlet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Dimensions

Height 76 mm

Width 43 mm

Length 93.5 mm

Ambient conditions

Degree of protection of housing (IP) IP65

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K

Type B16

Housing type Sleeve housing

Locking type With double locking latch

No. of cable outlets 1

Cable exit Lateral

Screw connection none

Type of the screw connection 1x M32

Housing material Aluminum die-cast

Housing surface material Powder-coated, gray

Material lock Stainless steel, handle: PA

Material grip body interlock PA

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 16-TMQ-H-O1STM32S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.