

**INDUSTRIAL COMPONENT DATA**

# HC-HPR-B24-HHWH-1TTM40-EM-BK 1411062 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-HPR-B24-HHWH-1TTM40-EM-BK



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | PHOENIX CONTACT                    |
| MPN / Reference | HC-HPR-B24-HHWH-1TTM40-EM-BK       |
| Catalog number  | 1411062                            |
| Category        | Housing for rectangular connectors |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-10772CE1EC                      |
| Generated       | 2026-08-06                         |

## Product Overview

### Housing

HEAVYCON B24 Aerial Enclosure, HPR Series, Screw Locked, M40 Thread, Straight Outlet, for High EMC and Environmental Requirements

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

## Additional Product Information

### Key Commercial Data

Orderkey 1411062

Packing unit 1 pc

Catalog page Page 629 (C-4-2015)

GTIN 4046356921671

Weight per Piece (excluding packing) 730.000 g

Custom tariff number 85389099

Country of origin CN (China)

### Dimensions

Height 110.5 mm

Width 59.2 mm

Length 192 mm

Ambient conditions

Degree of protection of housing (IP) IP66

IP68 (0.5 bar / 24 h)

IP69K (ISO 20653:2013-02)

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-B24, BB46, BBB64, D64, DD108, M

Size B24

Housing type Sleeve housing

Color black

Locking type with screw locking

No. of cable outlets 1

Cable outlet straight

Screw connection none

Type of the screw connection 1x M40

Protective cover no

Housing material Aluminum die-cast

Housing surface material Powder-coated, black

Material of locking screw Stainless steel

Assembly instructions M6 locking screw, slotted hexagon head screw (SW10), tightening torque: 4 Nm

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202

ETIM 4.0EC000437ETIM 5.0EC000437ETIM 6.0EC000437

UNSPSC 13.231261501

ETIM for 1411062 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

59.2 mm

Height (EF000040)

110.5 mm

Depth (EF000049)

192 mm

Type of housing (EF006980)

Plug case

Housing material (EF001596)

Aluminium....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-HPR-B24-HHWH-1TTM40-EM-BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.