

INDUSTRIAL COMPONENT DATA

HC-A 16-EBUC-32 1677050 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-A 16-EBUC-32



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-A 16-EBUC-32
Catalog number	1677050
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-074F6FC205
Generated	2026-08-01

Product Overview

Contact insert

Insert of females HEAVYCON, series A16, 16 poles, connection set, numbering of 17 ... 32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1677050

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 515 (C-2-2017)

GTIN 4017918129675

Weight per Piece (excluding packing) 45.640 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Note For HC-D25 / HC-D50 housing, crimp contact CK2,5-ED (crimp contacts not included in scope of supply)

Connectors may be operated only when there is no load/voltage.

Connection method Crimp connection

Degree of pollution 3

Overvoltage category III

Number of positions 16+PE
Insertion/withdrawal cycles ≥ 500
Size D25
Contact numbering 17 - 32
Conductor cross section 0.14 mm² ... 4 mm² (applies to stranded conductors)
Connection cross section AWG 20 ... 12
Stripping length of the individual wire 8 mm
Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required
Ambient conditions
Ambient temperature (operation) -40 °C ... 125 °C (including heating up of contacts)
Material data
Contact material Copper alloy
Contact surface material Ag (alternatively Au)
Contact carrier material PA
Electrical characteristics
Rated voltage (III/3) 250 V
Rated surge voltage 4 kV
Rated current 16 A
Standards and Regulations
Connection in acc. with standard CSA
Constructional and testing regulations DIN VDE 0627/86
DIN VDE 0110/02.79
DIN VDE 0110-1/04.97
IEC 60664-1, DIN IEC 60512
IEC 60352
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally fri...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-A 16-EBUC-32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.