

INDUSTRIAL COMPONENT DATA

HC-D 15-EBUC-R 1679511 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-D 15-EBUC-R



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-D 15-EBUC-R
Catalog number	1679511
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-85E60A2BA9
Generated	2026-08-04

Product Overview

Contact insert

HEAVYCON female insert, D15 series, 15 poles, crimped connection, stamped contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1679511

Packing unit 10 pc

Catalog page Page 419 (C-4-2013)

GTIN 4017918163747

Weight per Piece (excluding packing) 35.650 g

Custom tariff number 85366990

Country of origin CZ (Czech Republic)

General

Note For HEAVYCON housing of type D15

Connection method Crimp connection

Degree of pollution 3

Overvoltage category III

Number of positions 15+PE

Insertion/withdrawal cycles >= 500

Size D15

Conductor cross section 0.14 mm² ... 1.5 mm²

Connection cross section AWG 26 ... 16

Stripping length of the individual wire 3 mm +0,5 mm (0,14 mm² ... 0,5 mm²)

3.5 mm +1 (0.5 mm² ... 1.5 mm²)

Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required

Connection Connectors may be plugged in only when there is no load/voltage.

Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C (including heating up of contacts)

Material data

Contact material Copper alloy

Contact surface material Ag (alternatively Au)

Contact carrier material PC

Electrical characteristics

Rated voltage (III/3) 250 V

Rated surge voltage 4 kV

Rated current 10 A

Standards and Regulations

Connection in acc. with standard CSA

Constructional and testing regulations DIN VDE 0627/86

DIN VDE 0110/02.79

DIN VDE 0110-1/04.97

IEC 60664-1, DIN IEC 60512

IEC 60352

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold v...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-D 15-EBUC-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.