


INDUSTRIAL COMPONENT DATA

HC-K 4/8-EBUS 1679320 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-K 4/8-EBUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-K 4/8-EBUS
Catalog number	1679320
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-A6A3C0318A
Generated	2026-08-03

Product Overview

Contact insert

Contact insert, number of poles: 4+8+2PE, size: B24, power contacts: 4, control contacts: 8, Female, Screw connection, 400 V, 80 A, 1.5 mm² ... 16 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1679320

Packing unit 1 pc

Catalog page Page 557 (C-2-2017)

GTIN 4017918163563

Weight per Piece (excluding packing) 148.500 g

Custom tariff number 85366990

Country of origin RO (Romania)

General

Note For housing HC-B24

Connection method Screw connection (power contacts)

Screw connection (control contacts)

Tightening torque 2 Nm (Power contact, 2.5 mm²)3 Nm (Power contact, 4 ... 16 mm²)

1.2 Nm (Power contact, 1.5 mm²)
0.5 Nm (control contacts)
Screwdriver blade 0.8 x 4.5 mm (power contacts)
0.5 x 3.5 mm (control contacts)
Degree of pollution 3
Overvoltage category III
Number of positions 4+8+2PE
No. of power contacts 4
No. of control contacts 8
Insertion/withdrawal cycles >= 500
Size B24
Contact numbering 1 - 4
Conductor cross section 1.5 mm² ... 16 mm² (power contacts)
0.5 mm² ... 2.5 mm² (control contacts)
Connection cross section AWG 16 ... 6 (power contacts)
20 ... 14 (control contacts)
Stripping length of the individual wire 14 mm (Power contact)
7 mm (control contact)
Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required
Connection Use wire end protection (screw connections do not have wire protection)
Ambient conditions
Ambient temperature (operation) -40 °C ... 125 °C
Material data
Contact material Copper alloy
Contact surface material Ag (alternatively Au)
Material of contact surface, power contact Ag
Material of contact surface, control contact Ag
Contact carrier material PA
Standa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-K 4/8-EBUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.