

INDUSTRIAL COMPONENT DATA

HC-B 16-TFL-H-O1STM32G 1460124 PHOENIX CONTACT HEAVYCON B16 sleeve housing, for single locking latch, height..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 16-TFL-H-O1STM32G



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 16-TFL-H-O1STM32G
Catalog number	1460124
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-871A639FFA
Generated	2026-08-05

Product Overview

HEAVYCON B16 sleeve housing, for single locking latch, height: 76 mm, with 1 x M32 thread, straight cable outlet
HEAVYCON B16 aerial housing, for longitudinal flange, height 76 mm, with 1x M32 thread, straight cable outlet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Dimensions

Height 76 mm

Width 43 mm

Length 94 mm

Ambient conditions

Degree of protection of housing (IP) IP65

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K

Type B16

Housing type Sleeve housing

Locking type for single locking latch

No. of cable outlets 1

Cable exit straight

Screw connection none

Type of the screw connection 1x M32

Housing material Aluminum die-cast

Housing surface material Powder-coated, gray

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 16-TFL-H-O1STM32G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.