

INDUSTRIAL COMPONENT DATA**HC-D 25-ESTC-R 1679472 PHOENIX CONTACT Contact insert**

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-D 25-ESTC-R



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-D 25-ESTC-R
Catalog number	1679472
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-E84D50EE74
Generated	2026-08-04

Product Overview

Contact insert

HEAVYCON male insert, D25 series, 25-pos., crimp connection, rolled contacts

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces****Additional Product Information**

Technical dataNotesGeneral For HC-D25 housing, crimp contacts CK1,6-ER (crimp contacts not included in scope of supply)

MountingAssembly note To ensure correct use, installation in housing with IP54 protection or better is required

Connectors may be plugged in only when there is no load/voltage.

Product propertiesProduct type Contact insert with a fixed no. of positions

Series HC-D

Type D25

D50

Number of positions 25

Connection profile 25+PE

Contact material type rolled

Insulation characteristics

Overvoltage category III

Degree of pollution 3

DimensionsDimensional drawing

Width 22.7 mm
Height 34 mm
Length 73 mm
Drill hole distance, horizontal 66 mm
Drill hole distance, vertical 16 mm
Mechanical characteristics
Contact diameter 1.6 mm
Connection dataConnection technology
Connection technology Crimp connection
Connection in acc. with standard IEC / EN
Conductor connection
Conductor cross section 0.14 mm² ... 1.5 mm²
Connection cross section AWG 26 ... 16
Stripping length of the individual wire 3 mm +0,5 mm (0.14 mm² ... 0.5 mm²)
3.5 mm +1 mm (0.5 mm² ... 1.5 mm²)
Electrical propertiesRated voltage (III/3) 250 V
Rated surge voltage 4 kV
Rated current 10 A
Test voltage 4 kV AC
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 500
Material specificationsFlammability rating according to UL 94 V0
Contact material Copper alloy
Contact surface material Ag (alternatively Au)
Contact carrier material PC
Environmental and real-life conditionsAmbient conditions
Ambient t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-D 25-ESTC-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.