

INDUSTRIAL COMPONENT DATA

HC-K 6/36-ESTC 1636376 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-K 6/36-ESTC



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-K 6/36-ESTC
Catalog number	1636376
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-EC0A72CC6F
Generated	2026-08-04

Product Overview

Contact insert

Contact insert, number of poles: 6+36+PE, size: B16, power contacts: 6, control contacts: 36, Male, Crimped connection, 690 V, 40 A, 1.5 mm² ... 6 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1636376

Packing unit 1 pc

Catalog page Page 559 (C-2-2017)

GTIN 4046356011518

Weight per Piece (excluding packing) 65.600 g

Custom tariff number 85366990

Country of origin CN (China)

General

Note For HEAVYCON ADVANCE and HEAVYCON housing of type B16/B32, power contacts: CK 4,0-ED, control contacts:

CK 1,6-ED (crimp contacts not supplied as standard)

Connection method Crimp connection (power contacts)

Crimp connection (control contacts)

Degree of pollution 3

Overvoltage category III

Number of positions 6+36+PE

No. of power contacts 6

No. of control contacts 36

Insertion/withdrawal cycles ≥ 500

Size B16

Contact numbering 1 - 6

Conductor cross section 1.5 mm² ... 6 mm² (power contacts)

0.14 mm² ... 2.5 mm² (control contacts)

Connection cross section AWG 16 ... 10 (power contacts)

26 ... 14 (control contacts)

Stripping length of the individual wire 9 mm (Power contacts, with a cross section of 1.5 mm² ... 2.5 mm²)

8 mm (Control contacts, with a cross section of 0.14 mm² ... 1.5 mm²)

9.5 mm (power contacts, with a cross section of 4 mm² ... 6 mm²)

6 mm (Control contacts, with a cross section of 2.5 mm²)

Wire diameter including insulation 5 mm

Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required

Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C

Material data

Contact material Cu alloy

Material of contact surface, power contact Ag

Material of contact surface, control contact Ag...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-K 6/36-ESTC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.