


INDUSTRIAL COMPONENT DATA

HC-BB32-I-CT-M 1584732 PHOENIX CONTACT HEAVYCON pin insert, series: BB32, 32-pos., crimp connection, with pl..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-BB32-I-CT-M



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-BB32-I-CT-M
Catalog number	1584732
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-08091DFBB5
Generated	2026-08-05

Product Overview

HEAVYCON pin insert, series: BB32, 32-pos., crimp connection, with plastic coding profile, can be coded
Contact insert, number of poles: 32+PE, size: B16, number of connections per pole: 1, Male, Crimped connection, 500 V, 16 A, 0.5 mm² ... 4 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

General

Note For HC-B16 housing, crimp contacts CK 2,5-ED (crimp contacts not included in scope of supply)

Connection method Crimp connection

Pollution degree 3

Overvoltage category III

Number of positions 32+PE

Insertion/withdrawal cycles >= 500

Type B16

Connection in acc. with standard IEC / EN

Conductor cross section 0.5 mm² ... 4 mm²

Connection cross section AWG 20 ... 12

Stripping length of the individual wire 7.5 mm

Assembly instructions - Housing heights of h >= 72 mm are recommended when there is a high number of wires.

Connection Connectors may only be inserted when there is no load/the power is switched off. Contact release by means of CK2,5-EWZ (Order No. 1662722)

Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C (including heating up of contacts)

Material data

Flammability rating according to UL 94 V0

Contact material Copper alloy

Contact surface material Ag (alternatively Au)

Contact carrier material PC

Standards/regulations PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2

(Risk level HL1 - HL3)

Electrical characteristics

Rated voltage (III/3) 500 V

Rated surge voltage 6 kV

Rated current 16 A

ETIM for 1584732 Connectors (EC000438)

Feature Name

Feature Value

Number of power contacts (EF012216)

32

Number of control contacts (EF012217)

0

Contact insert without contacts (EF007324)

Yes

Contact type (EF001587)

Pin

Number of poles (EF001391)

32

Diameter plug-in contact (EF007320)

2.5 mm

Material connector...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-BB32-I-CT-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.