


INDUSTRIAL COMPONENT DATA

HC-B10-I-PT-F 1407729 PHOENIX CONTACT HEAVYCON socket insert, B10 series, 10 + PE-pos., push-in connection

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B10-I-PT-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B10-I-PT-F
Catalog number	1407729
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-07AECC1B58
Generated	2026-08-05

Product Overview

HEAVYCON socket insert, B10 series, 10 + PE-pos., push-in connection

Contact insert, number of poles: 10+PE, size: B10, number of connections per pole: 1, Female, Push-in connection, 500 V, 16 A, 0.14 mm² ... 2.5 mm², Application: Power

Contact insert, number of positions: 10+PE, size: B10, number of connections per position: 1, Socket, Push-in connection, 500 V, 16 A, 0.14 mm² ... 2.5 mm², application: Power

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral only use flexible conductors with ferrules

General Connectors may be operated only when there is no load/voltage.

MountingAssembly note To ensure correct use, installation in housing with IP54 protection or better is required

Product propertiesProduct type Contact insert with a fixed no. of positions

Series HC-B

Application Power

Type B10

Number of positions 10

Connection profile 10+PE

Contact numbering 1 - 10

Number of connections per position 1

Contact material type rolled
Data management status
Article revision 08
Insulation characteristics
Overvoltage category III
Degree of pollution 3
DimensionsDimensional drawing
Width 34 mm
Height 37 mm
Length 64 mm
Drill hole distance, horizontal 57 mm
Drill hole distance, vertical 27 mm
Mechanical characteristics
Contact diameter 2.5 mm
Connection dataConnection technology
Connection technology Push-in connection
Number of connections per position 1
Connection in acc. with standard IEC / EN
Conductor connection
Conductor cross section 0.14 mm² ... 2.5 mm²
Connection cross section AWG 26 ... 14
Tightening torque 0.8 Nm ... 1.2 Nm (PE connection)
0.5 Nm ... 0.8 Nm (Mounting screws for mounting in the HEAVYCON housing)
Stripping length 8 mm ... 10 mm
Electrical propertiesRated voltage (III/3) 500 V
Rated surge voltage 6 kV
Rated current 16 A (power contacts)
SCCR 5 kA (UL 2237)
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 500
Material specificationsFlammability rating according to UL 94....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B10-I-PT-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.