


## INDUSTRIAL COMPONENT DATA

# HC-BB10-I-CT-F 1584703 PHOENIX CONTACT HEAVYCON socket insert, series: BB10, 10-pos., crimp connection, with..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-BB10-I-CT-F



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                           |
| MPN / Reference | HC-BB10-I-CT-F                            |
| Catalog number  | 1584703                                   |
| Category        | Contact insert for rectangular connectors |
| Minimum order   | 1 Pcs                                     |
| Document ID     | EO-7CDDF33C49                             |
| Generated       | 2026-08-03                                |

## Product Overview

HEAVYCON socket insert, series: BB10, 10-pos., crimp connection, with plastic coding profile, can be coded  
Contact insert, number of poles: 10+PE, size: B6, number of connections per pole: 1, Female, Crimped connection, 500 V, 16 A, 0.5 mm<sup>2</sup> ... 4 mm<sup>2</sup>  
Contact insert, number of positions: 10+PE, size: B6, number of connections per position: 1, Socket, Crimp connection, 500 V, 16 A, 0.5 mm<sup>2</sup> ... 4 mm<sup>2</sup>

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                            |
|--------------|------------------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Industrial plug-in connectors/interfaces |
|--------------|------------------------------------------------------------|

## Additional Product Information

Technical dataNotesGeneral For HEAVYCON ADVANCE and HEAVYCON housing of B6 type, crimp contacts CK 2,5-ED (crimp contacts not included in the scope of supply).

General Connectors may be operated only when there is no load/voltage.

MountingAssembly note To ensure correct use, installation in housing with IP54 protection or better is required

Product propertiesProduct type Contact insert with a fixed no. of positions

Series HC-BB

Type B6

Number of positions 10

Connection profile 10+PE

Contact numbering 1 - 10

Number of connections per position 1

Contact material type turned  
Data management status  
Article revision 04  
Insulation characteristics  
Overvoltage category III  
Degree of pollution 3  
DimensionsDimensional drawing  
Width 34 mm  
Height 32.5 mm  
Length 51 mm  
Drill hole distance, horizontal 44 mm  
Drill hole distance, vertical 27 mm  
Mechanical characteristics  
Minimum housing height 72 mm  
Contact diameter 2.5 mm  
Connection dataConnection technology  
Connection technology Crimp connection  
Number of connections per position 1  
Connection in acc. with standard IEC / EN  
Conductor connection  
Conductor cross section 0.5 mm<sup>2</sup> ... 4 mm<sup>2</sup>  
Connection cross section AWG 20 ... 12  
Tightening torque 0.8 Nm ... 1.2 Nm (PE connection)  
0.5 Nm ... 0.8 Nm (Mounting screws for mounting in the HEAVYCON housing)  
Stripping length of the individual wire 7.5 mm  
Electrical propertiesRated voltage (III/3) 500 V  
Rated surge voltage 6 kV  
Rated current 16 A  
Mechanical propertiesMechanical data  
Insertion/withdrawal...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-BB10-I-CT-F with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.