

**INDUSTRIAL COMPONENT DATA**

# PTPOWER 95-3L-F 3260121 PHOENIX CONTACT High-current terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTPOWER 95-3L-F



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | PTPOWER 95-3L-F             |
| Catalog number  | 3260121                     |
| Category        | Feed-through terminal block |
| Minimum order   | 3 Pcs                       |
| Document ID     | EO-D9F9AE8FA2               |
| Generated       | 2026-08-03                  |

## Product Overview

High-current terminal block

Current terminal, locked, rated voltage: 1000 V, rated current: 232 A, number of connections: 6, number of poles: 3, connection type: PowerTurn connection, 1st floor, cross-section: 25 mm<sup>2</sup> - 95 mm<sup>2</sup>, mounting type: direct screwed, color: gray

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 3260121

Packing unit 3 pc

Minimum order quantity 3 pc

Note Made to Order (non-returnable)

Catalog page Page 129 (C-1-2017)

GTIN 4046356778992

Weight per Piece (excluding packing) 621.800 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of positions 3

Number of levels 1  
Number of connections 6  
Potentials 3  
Nominal cross section 95 mm<sup>2</sup>  
Color gray  
Insulating material PA  
Flammability rating according to UL 94 V0  
Rated surge voltage 8 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation for nominal condition 7.54 W  
Maximum load current 232 A (with 95 mm<sup>2</sup> conductor cross section)  
Nominal current I<sub>N</sub> 232 A  
Nominal voltage U<sub>N</sub> 1000 V AC  
1500 V DC  
Open side panel No  
Relative insulation material temperature index (Elec., UL 746 B) 130 °C  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C  
Static insulating material application in cold -60 °C  
Behavior in fire for rail vehicles (DIN 5510-2) Test passed  
Flame test method (DIN EN 60695-11-10) V0  
Oxygen index (DIN EN ISO 4589-2) >32 %  
NF F16-101, NF F10-102 Class I 2  
NF F16-101, NF F10-102 Class F 2  
Surface flammability NFPA 130 (ASTM E 162) passed  
Specific optical density of smoke NFPA 130 (ASTM E 662) passed  
Smoke gas toxicity NFPA 130 (SMP 800C) passed  
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg  
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3  
Fire protection for rail vehic...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTPower 95-3L-F with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.