

INDUSTRIAL COMPONENT DATA

PTPOWER 50 P 3260065 PHOENIX CONTACT High-current terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTPOWER 50 P



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTPOWER 50 P
Catalog number	3260065
Category	Feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-372AC8359B
Generated	2026-08-01

Product Overview

High-current terminal block

Power terminal block, with test socket, nominal voltage: 1000 V, nominal current: 150 A, number of connections: 2, number of poles: 1, connection type: PowerTurn connection, 1st floor, cross-section: 10 mm² - 70 mm², mounting class: NS 35/15, colour: grey

High-current terminal block, with test socket, nom. voltage: 1000 V, nominal current: 150 A, number of connections: 2, number of positions: 1, connection method: PowerTurn connection, 1 level, cross section: 10 mm² - 70 mm², mounting type: NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Technical dataProduct propertiesProduct type High current terminal block

Number of positions 1

Number of connections 2

Number of rows 1

Potentials 1

Data management status

Article revision 09

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Rated surge voltage 8 kV

Maximum power dissipation for nominal condition 4.73 W

Connection data Number of connections per level 2

Nominal cross section 50 mm²

Rated cross section AWG 2/0

1 level

Stripping length 30 mm ... 32 mm

Internal cylindrical gage A10

Connection in acc. with standard IEC 60947-7-1

Conductor cross section rigid 10 mm² ... 70 mm²

Cross section AWG 6 ... 2/0 (converted acc. to IEC)

Conductor cross section flexible 10 mm² ... 70 mm²

Conductor cross section, flexible [AWG] 6 ... 2/0 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 10 mm² ... 50 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 10 mm² ... 50 mm²

Cross-section with insertion bridge, rigid 10 mm² ... 50 mm²

Cross-section with insertion bridge, flexible 10 mm² ... 50 mm²

Cross-section with insertion bridge, flexible, with ferrule without plastic sleeve 10 mm² ... 50 mm²

Cross-section with insertion bridge, flexible, with ferrule with plastic sleeve 10 mm² ... 50 mm²

Nominal current 150 A

Maximum load current 150 A (with 50 mm² conductor cross section)

Nominal voltage 1000 V

1 level Connection cross sections directly pluggable

Conductor cross section rigid 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTPower 50 P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.