

**INDUSTRIAL COMPONENT DATA**

# PTPOWER 35-3L/N 3212069 PHOENIX CONTACT High-current terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTPOWER 35-3L/N



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | PTPOWER 35-3L/N             |
| Catalog number  | 3212069                     |
| Category        | Feed-through terminal block |
| Minimum order   | 2 Pcs                       |
| Document ID     | EO-D2093C32D7               |
| Generated       | 2026-08-02                  |

## Product Overview

High-current terminal block

Power terminal, locked, nominal voltage: 1000 V, nominal current: 125 A, number of connections: 8, number of poles: 4, connection type: PowerTurn connection, Dimensioning cross-section: 35 mm<sup>2</sup>, cross-section: 2.5 mm<sup>2</sup> - 35 mm<sup>2</sup>, mounting class: NS 35/15, colour: grey/blue

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

Key Commercial Data

Orderkey 3212069

Packing unit 2 pc

Minimum order quantity 2 pc

Catalog page Page 125 (C-1-2017)

GTIN 4046356869553

Weight per Piece (excluding packing) 345.800 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of positions 4

Number of levels 1

Number of connections 8  
Potentials 4  
Nominal cross section 35 mm<sup>2</sup>  
Color gray/blue  
Insulating material PA  
Flammability rating according to UL 94 V0  
Rated surge voltage 8 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation for nominal condition 4.06 W  
Maximum load current 125 A (with 35 mm<sup>2</sup> conductor cross section)  
Nominal current I<sub>N</sub> 125 A  
Nominal voltage U<sub>N</sub> 1000 V  
Open side panel No  
Relative insulation material temperature index (Elec., UL 746 B) 130 °C  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C  
Static insulating material application in cold -60 °C  
Behavior in fire for rail vehicles (DIN 5510-2) Test passed  
Flame test method (DIN EN 60695-11-10) V0  
Oxygen index (DIN EN ISO 4589-2) >32 %  
NF F16-101, NF F10-102 Class I 2  
NF F16-101, NF F10-102 Class F 2  
Surface flammability NFPA 130 (ASTM E 162) passed  
Specific optical density of smoke NFPA 130 (ASTM E 662) passed  
Smoke gas toxicity NFPA 130 (SMP 800C) passed  
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg  
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3  
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3  
Fire p...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTPower 35-3L/N with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.