

INDUSTRIAL COMPONENT DATA

ME 22,5 F-UT GN 2854131 PHOENIX CONTACT Mounting base housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 F-UT GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 F-UT GN
Catalog number	2854131
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-3E30C3AD62
Generated	2026-08-02

Product Overview

Mounting base housing

Rail box, Bottom of housing with metal pin, flat design, with ventilation slits, width: 22.6 mm, height: 99 mm, depth: 84.8 mm, color: green (6021), cross bridge: without bus connector, number of poles cross connector: not relevant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

Additional Product Information

Key Commercial Data

Orderkey 2854131

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 659 (C-1-2013)

GTIN 4017918190163

Weight per Piece (excluding packing) 30.940 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Housing type Component housing

Housing material Polyamide

Color (RAL) green

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Dimensions

Width 22.5 mm

Depth 84.8 mm

Height 99 mm

Technical data

Power dissipation without gap 5.9 W

Power dissipation with 20 mm gap 11.5 W

Number of positions 16

24

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

ClassificationseCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss
7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC001031ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC

13.231261501

ETIM for 2854131 Low-voltage industrial controls and switchgear (EC002779)

Feature Name**Feature Value**

Type of enclosure (EF003086)

Closed

Housing connectable (EF003088)

No

Material (EF002169)

Other

Surface finishing (EF006569)

Other

Colour (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend PHOENIX CONTACT / ME 22,5 F-UT GN with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.**GLOBAL OFFICES**Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, DubaiCatalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.