


INDUSTRIAL COMPONENT DATA

BC 161,6 OT U11 KMGY 2278513 PHOENIX CONTACT Upper part of housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 161,6 OT U11 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 161,6 OT U11 KMGY
Catalog number	2278513
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-B677C08802
Generated	2026-08-03

Product Overview

Upper part of housing

Rail box for use in installation distributors according to DIN 43880, Top of the housing (U11) with ventilation slits, Installation depth of connection technology: 11.1 mm, width: 161.6 mm, height: 89.7 mm, depth: 54.85 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data

Orderkey 2278513

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 700 (C-1-2013)

GTIN 4046356299480

Weight per Piece (excluding packing) 51.630 g

Custom tariff number 85472000

Country of origin DE (Germany)

Item properties

Brief article description Upper part of housing

Type BC 161,6 OT U11 KMGY

Order No. 2278513

Housing type Installation component housing

Type Upper part

Dimensions

Width [w] 161.6 mm

Height [h] 89.7 mm

Depth [d] 54.85 mm

Material data

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polycarbonate

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Packaging information

Pieces per package 10

Denomination packing units Pcs.

Standards and regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss

7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC001031ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC

13.231261501

ETIM for 2278513 Low-voltage industrial controls and switch...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 161,6 OT U11 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.