

INDUSTRIAL COMPONENT DATA

HC-B 10-TMB-100/O1STM25G-EEE 1460365 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 10-TMB-100/O1STM25G-EEE



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 10-TMB-100/O1STM25G-EEE
Catalog number	1460365
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-12F38AE2EE
Generated	2026-08-05

Product Overview

Housing

HEAVYCON ADVANCE B10 bobbin housing, with bayonet lock (inner hexagon) in stainless steel, seawater resistant aluminium, height 100 mm, with 1x M25 thread, straight cable outlet, no surface; conductive joint (CEM characteristics)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1460365

Packing unit 10 pc

Catalog page Page 568 (PC-2011)

GTIN 4046356592642

Weight per Piece (excluding packing) 346.050 g

Custom tariff number 85389099

Country of origin DE (Germany)

Dimensions

Height 100 mm

Width 57 mm

Length 105 mm

Ambient conditions

Degree of protection of housing (IP) IP66

IP67

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-B10, BB18, DD42, M, K8/24

Size B10

Housing type Sleeve housing

Color gray aluminum

Locking type Bayonet locking

Fixing screws M6

No. of cable outlets 1

Cable outlet straight

Screw connection none

Type of the screw connection 1x M25

Housing material Die-cast aluminum, corrosion resistant

Housing surface material uncoated

Seal material NBR, conductive

Material lock Stainless steel

Connection If insulating powder coating is present on the control cabinet panel, it should be removed from the profile gasket area in order to ensure optimum shielding.

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027140816eCl@ss 4.127140816eCl@ss 5.027143424eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss

7.027440202eCl@ss 8.027440202eCl@ss 9.027440202

ETIM 4.0EC000437ETIM 5.0EC000437ETIM 6.0EC000437

UNSPSC 6.0131261502UNSPSC 7.090131261502UNSPSC 1131261502UNSPSC 12.0131261502UNSPSC

13.231261501

ETIM for 1460365 Connectors (EC000437)

Feature Name

Feature Value

Width (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 10-TMB-100/O1STM25G-EEE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.