

INDUSTRIAL COMPONENT DATA

ME MAX 12,5 3-3 TBUS KMGY 2279020 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 12,5 3-3 TBUS KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 12,5 3-3 TBUS KMGY
Catalog number	2279020
Category	Electronic enclosure
Minimum order	10 Pcs
Document ID	EO-251E85F245
Generated	2026-08-02

Product Overview

Electronic housing

Rail box, Metal pin complete box, high design, with TBUS option, with ventilation slits, width: 12.6 mm, height: 99 mm, depth: 113.65 mm, colour: light grey (7035), cross bridge: Rail bus connector (optional), number of poles cross connector: 5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data

Orderkey 2279020

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 684 (C-1-2013)

GTIN 4046356180580

Weight per Piece (excluding packing) 46.010 g

Custom tariff number 85389099

Country of origin DE (Germany)

Item properties

Brief article description Electronic housing

Type ME MAX 12,5 3-3 TBUS KMGY

Order No. 2279020

Housing type DIN rail housing
Type Tall design
Max. IP code to attain IP20
Mounting type DIN rail mounting
Number of levels 3
Ventilation openings present yes
Max. number of positions 18 (pitch: 3.5 mm)
12 (pitch: 5 mm)
Dimensions
Dimensional drawing
Width [w] 12.5 mm
Height [h] 99 mm
Depth [d] 114.5 mm
Depth from top edge of DIN rail [d] 107 mm
Material data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material Polyamide
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
PCB data
Number of PCB holders 1
Mounting position Vertical (horizontal DIN rail)
Type of PCB mount Latching
Power dissipation, single housing at 20 °C
Ambient temperature 20 °C
Reduction factor 1
Mounting position vertical
Power dissipation 4.4 W
Power dissipation, single housing at 30 °C
Ambient temperature 30 °C
Reduction factor 0.91
Mounting position vertical
Power dissipation 4 W
Power dissipation, single housing at 4...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 12,5 3-3 TBUS KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.