

INDUSTRIAL COMPONENT DATA

ME 67,5 UT/FE BUS/10+2 KMGY 2200541 PHOENIX CONTACT

Mounting base housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 67,5 UT/FE BUS/10+2 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 67,5 UT/FE BUS/10+2 KMGY
Catalog number	2200541
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-37202A6A4D
Generated	2026-08-03

Product Overview

Mounting base housing

Rail box, Bottom of the box with metal pin, with 3 FE contacts, high design, with ventilation slits, width: 67.8 mm, height: 99 mm, depth: 107.3 mm, color: light gray (7035), cross bridge: integrated bus connector, number of poles cross connector: 10+2, Bus connector: 10 parallel contacts, 2 series contacts

DIN rail housings, housing base with metal mounting foot, with 3 FE contacts, high type, with ventilation slots, width: 67.8 mm, height: 99 mm, depth: 107.3 mm, colour: light grey (similar to RAL 7035), cross connection: integrated bus connector, no. of poles cross connector: 10+2, bus connector: 10 parallel contacts, 2 serial contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

Additional Product Information

Key Commercial Data

Orderkey 2200541

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 665 (C-1-2013)

GTIN 4046356608077

Weight per Piece (excluding packing) 117.540 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Housing type Component housing

Housing material Polyamide

Color (RAL) light gray (7035)

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Dimensions

Length 99 mm

Height 114.5 mm

Width 67.5 mm

Depth 99 mm

Technical data

Power dissipation without gap 9.1 W

Power dissipation with 20 mm gap 17.5 W

Number of positions 48

12

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss

7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC001031ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC

13.231261501

ETIM for 2200541 Low-voltage industrial controls and switchgear (EC002779)

Feature Name**Feature Value**

Type of enclosure (EF003086)

Closed

Housing connectable (EF003088)

No

Material (EF002169)

Other

Surface f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 67,5 UT/FE BUS/10+2 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.