

## INDUSTRIAL COMPONENT DATA

# HS LC-D3,2PL-7 1474362 PHOENIX CONTACT Single, passive, rigid light conductor, Cylindrical head, radiant sur..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HS LC-D3,2PL-7



|                 |                                                   |
|-----------------|---------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                   |
| MPN / Reference | HS LC-D3,2PL-7                                    |
| Catalog number  | 1474362                                           |
| Category        | Accessories/spare parts for industrial connectors |
| Minimum order   | 1000 Pcs                                          |
| Document ID     | EO-B65332B99E                                     |
| Generated       | 2026-08-05                                        |

## Product Overview

Single, passive, rigid light conductor, Cylindrical head, radiant surface: flat, number of indicators: 1, (1 row, 1 column), length: 7 mm, ESD protection:

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Technical dataNotesGeneral Refer to the data sheet for the range in the download area.

General Distance between LED and light guide of 0.2 mm.

Product propertiesProduct type Fiber optic

Number of positions 1

Alignment Vertical

Type passive, rigid

Conductor type Single light guide

Head form Cylinder head

Number of indicators 1 (1 row x 1 column)

Electrical propertiesESD protection < 4 kV

Connection dataCross section AWG (converted acc. to IEC)

DimensionsLength 7 mm

Diameter 3.2 mm

Hole diameter 2.8 mm

Dimensions 3 mm (Press-in length)

Material specificationsColor Lichtleiter transparent

Color (Light guide) transparent

Insulating material Polycarbonat

Environmental and real-life conditionsAmbient conditions

Max. IP code to attain IP20

Ambient temperature (operation) -40 °C ... 85 °C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HS LC-D3,2PL-7 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.