

**INDUSTRIAL COMPONENT DATA**

# HS LC-D5CS-38,2 1549673 PHOENIX CONTACT Single, passive, rigid light conductor, Countersunk head, Radiant su..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HS LC-D5CS-38,2



|                 |                                                   |
|-----------------|---------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                   |
| MPN / Reference | HS LC-D5CS-38,2                                   |
| Catalog number  | 1549673                                           |
| Category        | Accessories/spare parts for industrial connectors |
| Minimum order   | 4000 Pcs                                          |
| Document ID     | EO-ABED9E3140                                     |
| Generated       | 2026-08-04                                        |

## Product Overview

Single, passive, rigid light conductor, Countersunk head, Radiant surface: flat, Number of indicators: 1, (1 row, 1 column), length: 38.2 mm, ESD protection:

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Technical dataNotesGeneral Look at the series datasheet in the download area.

General Distance between LED and light conductor: 0.2 mm.

Item PropertiesProduct Type Fiber Optic

Number of poles 1

Orientation vertical

Execution passive, rigid

Yarn Type Simple Light Driver

Head Shape Countersunk head

Number of indicators 1 (1 row x 1 column)

Electrical PropertiesESD Protection < 4 kV

Connection dataAWG Conductor Section (Converted according to IEC)

DimensionsLongitude 38.2 mm

Diameter 5 mm

Drill Diameter 4.2 mm

Dimensions 3 mm (Snap Fit Length)

Material DataColour transparent

Insulating material Polycarbonat

Environmental and life-life conditionsEnvironmental conditions

Maximum achievable IP code IP20

Ambient Temperature (Service) -40 °C ... 85 °C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HS LC-D5CS-38,2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.