

INDUSTRIAL COMPONENT DATA

HS LC-H-D2C/ R4XC2-2,54 1071316 PHOENIX CONTACT Light guides, passive, rigid, can be used for the ME, ME-MAX..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HS LC-H-D2C/ R4XC2-2,54



Manufacturer	PHOENIX CONTACT
MPN / Reference	HS LC-H-D2C/ R4XC2-2,54
Catalog number	1071316
Category	Accessories/spare parts for industrial connectors
Minimum order	100 Pcs
Document ID	EO-BB3F6F84D1
Generated	2026-08-06

Product Overview

Light guides, passive, rigid, can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed)

Multi-light conductor with excessive radiation protection, passive, rigid, can be used for ME, ME MAX, ME-IO, ME PLC and EH device lines (case processing required)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
 Orderkey 1071316
 Packing unit 1
 GTIN 4055626752747
 Custom tariff number 39269097
 Product properties
 Material specifications
 General information
 Standards and Regulations
 Dimensions
 Ambient conditions
 Packaging details

Classifications

Product properties

Brief article description Fiber optic

Type HS LC-H-D2C/ R4XC2-2,54

Order No. 1071316

Type passive, rigid

Alignment Horizontal

Number of displays 8 (4 rows x 2 columns)

ESD protection < 8 kV

Head form Round, conical

Back to topDimensions

Pitch 2.54 mm

Diameter 2 mm

Hole diameter 1.2 mm

Back to topMaterial specifications

Material PC

Color (RAL) transparent

black (9005)

Back to topAmbient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Back to topGeneral information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

The tops of the press-in pegs are conical to make installation easier.

To prevent glare, the system has an aperture. This also makes mixed colors possible.

Back to topPackaging details

Pieces per package 100

Denomination packing units Pcs.

Back to topStandards and Regulations

Flammability rating according to UL 94 HB

Back to topClassifications

eCI@ss

eCI@ss 5.1 27180506

eCI@ss 6.0 27180800

eCI@ss 7.0 27182702

eCI@ss 8.0 27182702

eCI@ss 9.0 27182702

Back to topETIM

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

Back to topUNSPSC

UNSPSC 13.2 31261501

UNSPSC 18.0 31261501

UNSPSC 19.0 31261501

UNSPSC 20.0 31261501

UNSPSC 21.0 31261501....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HS LC-H-D2C/ R4XC2-2,54 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.