

INDUSTRIAL COMPONENT DATA

HS LC-V-T-D4X5,2S-45 1082300 PHOENIX CONTACT Vertical 4 mm light guide, transparent, with spherical 5.2 mm r..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HS LC-V-T-D4X5,2S-45



Manufacturer	PHOENIX CONTACT
MPN / Reference	HS LC-V-T-D4X5,2S-45
Catalog number	1082300
Category	Accessories/spare parts for industrial connectors
Minimum order	1 Pcs
Document ID	EO-000B1A3E6F
Generated	2026-08-05

Product Overview

Vertical 4 mm light guide, transparent, with spherical 5.2 mm raised head, assembly for wall thicknesses from 1 mm, made of polycarbonate (UL 94-V0), installation length 45 mm, watertight, IP68 (EN 50529)

4 mm vertical light conductor, transparent, with 5.2 mm spherical lens head, mounting for wall reinforcement from 1 mm, polycarbonate (UL 94-V0), 45 mm mounting length, waterproof, IP68 (EN 50529)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1082300

Packing unit 1 pc

GTIN 4055626812540

Weight per Piece (excluding packing) 20.000 g

Custom tariff number 39269097

Country of origin DE (Germany)

Product properties

Material specifications

Packaging details

Classifications

Dimensions

[General information](#)

[Standards and Regulations](#)

[Product properties](#)

[Brief article description](#) Fiber optic

Type HS LC-V-T-D4X5,2S-45

Order No. 1082300

Type passive, rigid

Alignment Vertical

Number of displays 1 (1 row x 1 column)

Head form Round, spherical emission surface

Max. IP code to attain IP68

[Back to top](#)[Dimensions](#)

Length 47.5 mm

Diameter 5.2 mm

Hole diameter 4.6 mm

[Back to top](#)[Material specifications](#)

Material PC

Color (RAL) transparent

[Back to top](#)[General information](#)

Type of note Assembly instruction:

Note The light guide is designed to be pressed into an H7-tolerated receptacle. Dry-install the LED display by pressing it in vertically. As an alternative, you can glue in the LED display, e.g., using LOCTITE 460.

Refer to the data sheet for the range in the download area.

[Back to top](#)[Packaging details](#)

Pieces per package 1

Denomination packing units Pcs.

[Back to top](#)[Standards and Regulations](#)

Flammability rating according to UL 94 HB

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 5.1 27180500

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

[Back to top](#)[ETIM](#)

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

[Back to top](#)[UNSPSC](#)

UNSPSC 13.2 31261501

UNSPSC 18.0 31261501

UNSPSC 19.0 31261501....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HS LC-V-T-D4X5,2S-45 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.