

## INDUSTRIAL COMPONENT DATA

# HS LCA-RD 12,5X5-L 1474410 PHOENIX CONTACT Signal light with braided wires, active, flexible, Cylindrical he..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HS LCA-RD 12,5X5-L



|                 |                                                                     |
|-----------------|---------------------------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                                     |
| MPN / Reference | HS LCA-RD 12,5X5-L                                                  |
| Catalog number  | 1474410                                                             |
| Category        | Accessories/spare parts for optic and acoustic signalling equipment |
| Minimum order   | 1 Pcs                                                               |
| Document ID     | EO-53E0AEED17                                                       |
| Generated       | 2026-08-03                                                          |

## Product Overview

Signal light with braided wires, active, flexible, Cylindrical head, radiant surface: flat, number of indicators: 1, (1 row, 1 column), diameter: 12.5 mm

Signal light with braided wires, active, flexible

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Technical dataNotesGeneral Refer to the data sheet for the range in the download area.

Product propertiesProduct type Light

Number of positions 1

Alignment flexible

Type active, flexible

Conductor type Signal light with litz wires

Head form Cylinder head

Number of indicators 1 (1 row x 1 column)

DimensionsDiameter 12.5 mm (Aperture diameter)

5 mm (Lens diameter)

Hole diameter 9.7 mm

Dimensions 100 mm (Cable ends)

Material specificationsColor Linse transparent

Color Gehäuse white

Insulating material PC

Environmental and real-life conditions Ambient conditions

Max. IP code to attain IP40

Ambient temperature (operation) -20 °C ... 80 °C

Packaging specifications Type of packaging PE bag

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HS LCA-RD 12,5X5-L with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.