

INDUSTRIAL COMPONENT DATA

HSC-LR 3U KIT 2003 2201797 PHOENIX CONTACT Mounting base housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HSC-LR 3U KIT 2003



Manufacturer	PHOENIX CONTACT
MPN / Reference	HSC-LR 3U KIT 2003
Catalog number	2201797
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-ECAAFB8701
Generated	2026-08-04

Product Overview

Mounting base housing

Rail box, 3U, Lock and Release System, width: 16.1 mm, height: 45.95 mm, depth: 8.8 mm, color: orange (2003)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2201797

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4046356911580

Weight per Piece (excluding packing) 3.790 g

Custom tariff number 85472000

Country of origin DE (Germany)

Item properties

Brief article description Mounting base housing

Type HSC-LR 3U KIT 2003

Order No. 2201797

Housing type Component housing

Type 3U

Mounting type Snap in

Dimensions

Width [w] 16.1 mm

Height [h] 45.95 mm

Depth [d] 8.8 mm

Material data

Color (RAL) orange

Flammability rating according to UL 94 V0

Housing material Polyamide

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

PCB data

Mounting position Vertical (horizontal DIN rail)

Packaging information

Pieces per package 10

Denomination packing units Pcs.

Standards and regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.027180506eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 4.0EC001031ETIM 5.0EC002638ETIM 6.0EC002638

UNSPSC 13.239121409

ETIM for 2201797 Low-voltage industrial controls and switchgear (EC002779)

Feature Name

Feature Value

Type of enclosure...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HSC-LR 3U KIT 2003 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.