

INDUSTRIAL COMPONENT DATA

ELR H3-IES-PT- 24DC/500AC-9 2903918 PHOENIX CONTACT

Hybrid motor starter

Brand: PHOENIX CONTACT | Manufacturer Part Number: ELR H3-IES-PT-24DC/500AC-9



Manufacturer	PHOENIX CONTACT
MPN / Reference	ELR H3-IES-PT-24DC/500AC-9
Catalog number	2903918
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-E0DA3582AC
Generated	2026-08-06

Product Overview

Hybrid motor starter

Hybrid start controller for starting 3~ AC motors up to 500 V AC and 9 A output current, with control voltage of 24 V DC, adjustable overload disconnect, emergency stop function up to SIL 3/PL e and push-in connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2903918

Packing unit 1 pc

Catalog page Page 30 (C-5-2017)

GTIN 4046356771412

Weight per Piece (excluding packing) 278.700 g

Custom tariff number 85371098

Country of origin DE (Germany)

Note

Type of note Notes on operation

Note If this device is to be used in combination with the CrossPowerSystem power distribution board, the device mount for the 16 A fuse (order designation: EM-CPS-DA-22,5F/16A; order number: 1002668) is required in order to attach the hybrid motor starter to the power distribution board.

Dimensions

Width 22.5 mm

Height 107.4 mm

Depth 113.7 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 70 °C (observe derating)

Ambient temperature (storage/transport) -40 °C ... 80 °C

Degree of protection IP20

Device supply

Rated control circuit supply voltage US 24 V DC

Control supply voltage range 19.2 V DC ... 30 V DC

Rated control supply current IS 40 mA

Type of protection Surge protection

Reverse polarity protection

Input data

Input name Control input

Rated actuating voltage UC 24 V DC

Triggering voltage range 19.2 V DC ... 30 V DC

Rated actuating current IC 5 mA (Input type 1)

Switching threshold 9.6 V ("0" signal)

19.2 V ("1" signal)

Switching level < 5 V DC (For EMERGENCY STOP)

Typical turn-off time < 30 ms

Type of protection Reverse polarity protection

Output data load output

Output name AC output

Rated operating voltage Ue 500 V AC

Operating voltage range 42 V AC ... 550 V AC

Rated operating current Ie 9 A (AC-51)

6.5 A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ELR H3-IES-PT-24DC/500AC-9 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.